#### **Chapter 5: CPU Scheduling**



**Operating System Concepts – 9**

**Silberschatz, Galvin and Gagne © 2013** 



- 1. Basic Concepts
- 2. Scheduling Criteria
- 3. Scheduling Algorithms
- 4. Thread Scheduling
- 5. Multiple-Processor Scheduling
- 6. Real-Time CPU Scheduling
- 7. Operating Systems Examples
- 8. Algorithm Evaluation





- To introduce CPU scheduling, which is the basis for multiprogrammed operating systems
- To describe various CPU-scheduling algorithms
- To discuss evaluation criteria for selecting a CPU-scheduling algorithm for a particular system
- To examine the scheduling algorithms of several operating systems





#### **5.1 BASIC CONCEPTS**



# **5.1.1 CPU-I/O Burst Cycle**

- In a single-processor system, only one process can run at a time. Others must wait until the CPU is free and can be rescheduled.
- objective of multiprogramming : to maximize CPU utilization
- CPU–I/O Burst Cycle Process execution consists of a **cycle** of CPU execution and I/O wait
- **CPU burst** followed by **I/O burst**
- CPU burst distribution is of main concern









## **5.1.3 Preemptive Scheduling**

- **Short-term scheduler** selects from among the processes in ready queue, and allocates the CPU to one of them
	- Queue may be ordered in various ways
- **CPU scheduling decisions** may take place when a process:
	- 1. Switches from running to waiting state
	- 2. Switches from running to ready state
	- 3. Switches from waiting to ready
	- 4. Terminates
- Scheduling under 1 and 4 is **nonpreemptive**
- All other scheduling is **preemptive**
	- Consider access to shared data
	- Consider preemption while in kernel mode
	- Consider interrupts occurring during crucial OS activities



- Dispatcher module gives control of the CPU to the process selected by the short-term scheduler; this involves:
	- switching context
	- switching to user mode
	- jumping to the proper location in the user program to restart that program

 **Dispatch latency** – time it takes for the dispatcher to stop one process and start another running





#### **5.2 SCHEDULING CRITERIA**





- **CPU utilization**  keep the CPU as busy as possible
- **Throughput** # of processes that complete their execution per time unit
- **Turnaround time**  amount of time to execute a particular process
- **Waiting time**  amount of time a process has been waiting in the ready queue
- **Response time**  amount of time it takes from when a request was submitted until the first response is produced, not output (for timesharing environment)



# **Scheduling Algorithm Optimization Criteria**

- Max CPU utilization
- Max throughput
- Min turnaround time
- Min waiting time
- Min response time
- for interactive systems (such as desktop systems), it is more important to minimize the variance in the response time than to minimize the average response time.
- An accurate illustration should involve many processes, each a sequence of **several hundred** CPU bursts and I/O bursts.
	- For simplicity, though, we consider **only one** CPU burst (in milliseconds) per process in our examples.





#### **5.3 SCHEDULING ALGORITHMS**



#### **5.3.1 First- Come, First-Served (FCFS) Scheduling**



Suppose that the processes arrive in the order:  $P_1$ ,  $P_2$ ,  $P_3$ The Gantt Chart for the schedule is:



- Waiting time for  $P_1 = 0$ ;  $P_2 = 24$ ;  $P_3 = 27$
- Average waiting time:  $(0 + 24 + 27)/3 = 17$





Suppose that the processes arrive in the order:

$$
P_2\,,\,P_3\,,\,P_1
$$

The Gantt chart for the schedule is:



- Waiting time for  $P_1 = 6$ ;  $P_2 = 0$ ,  $P_3 = 3$
- Average waiting time:  $(6 + 0 + 3)/3 = 3$
- Much better than previous case
- **Convoy effect**  short process behind long process
	- Consider one CPU-bound and many I/O-bound processes



# **5.3.2 Shortest-Job-First (SJF) Scheduling**

- Associate with each process the length of its next CPU burst
	- Use these lengths to schedule the process with the shortest time
- SJF is **optimal** gives minimum average waiting time for a given set of processes
	- The difficulty is **knowing** the length of the next CPU request
	- Could **ask** the user







SJF scheduling chart



Average waiting time =  $(3 + 16 + 9 + 0) / 4 = 7$ 



# **Determining Length of Next CPU Burst**

- Can only **estimate** the length should be similar to the previous one
	- Then pick process with shortest predicted next CPU burst
- Can be done by using the length of previous CPU bursts, using exponential averaging
	- 1.  $t_n$  = actual length of  $n^{th}$  CPU burst
	- 2.  $\tau_{n+1}$  = predicted value for the next CPU burst
	- 3.  $\alpha$ ,  $0 \leq \alpha \leq 1$
	- 4. Define:  $\tau_{n=1} = \alpha t_n + (1-\alpha)\tau_n$ .
- Commonly, α set to ½
- Preemptive version called **shortest-remaining-time-first**



#### **Prediction of the Length of the Next CPU Burst**





**Operating System Concepts – 9**

**th Edition 18 Silberschatz, Galvin and Gagne © 2013**

# **Examples of Exponential Averaging**

- $\alpha =0$ 
	- $\tau_{n+1} = \tau_n$
	- Recent history does not count
- $\alpha = 1$

$$
\bullet \quad \tau_{n+1} = \alpha \ t_n
$$

- Only the actual last CPU burst counts
- If we expand the formula, we get:

$$
\tau_{n+1} = \alpha \ t_n + (1 - \alpha)\alpha \ t_{n-1} + \dots
$$

$$
+ (1 - \alpha) \alpha \ t_{n-j} + \dots
$$

$$
+ (1 - \alpha) \frac{n+1}{\tau_0}
$$

Since both  $\alpha$  and (1 -  $\alpha$ ) are less than or equal to 1, each successive term has less weight than its predecessor





 Now we add the concepts of varying arrival times and preemption to the analysis



*Preemptive* SJF Gantt Chart



Average waiting time =  $[(10-1)+(1-1)+(17-2)+5-3)]/4 = 26/4 = 6.5$  msec





- A priority number (integer) is associated with each process
- The CPU is allocated to the process with the highest priority (smallest  $integer \equiv highest \, priority)$ 
	- Preemptive
	- Nonpreemptive
- SJF is priority scheduling where priority is the inverse of predicted next CPU burst time
- Problem  $=$  **Starvation** low priority processes may never execute
- Solution  $\equiv$  **Aging** as time progresses increase the priority of the process



### **Example of Priority Scheduling**



#### Priority scheduling Gantt Chart



Average waiting time  $= 8.2$  msec



## **5.3.4 Round Robin (RR)**

- Each process gets a small unit of CPU time (**time quantum** *q*), usually 10-100 milliseconds. After this time has elapsed, the process is preempted and added to the end of the ready queue.
- If there are *n* processes in the ready queue and the time quantum is *q*, then each process gets 1/*n* of the CPU time in chunks of at most *q* time units at once. No process waits more than (*n*-1)*q* time units.
- Timer interrupts every quantum to schedule next process
- **Performance** 
	- *q* large  $\Rightarrow$  FIFO
	- *q* small  $\Rightarrow$  *q* must be large with respect to context switch, otherwise overhead is too high



# **Example of RR with Time Quantum = 4**



The Gantt chart is:



- Typically, higher average turnaround than SJF, but better *response*
- q should be large compared to context switch time
- q usually 10ms to 100ms, context switch < 10 usec



## **Time Quantum and Context Switch Time**





#### **Turnaround Time Varies With The Time Quantum**



80% of CPU bursts should be shorter than q





- Ready queue is partitioned into separate queues, eg:
	- **foreground** (interactive)
	- **background** (batch)
- Process permanently in a given queue
- Each queue has its own scheduling algorithm:
	- foreground  $-RR$
	- background FCFS
- Scheduling must be done between the queues:
	- Fixed priority scheduling; (i.e., serve all from foreground then from background). Possibility of starvation.
	- Time slice each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR
	- 20% to background in FCFS



### highest priority system processes interactive processes interactive editing processes batch processes student processes

lowest priority

#### **th Edition 28 Silberschatz, Galvin and Gagne © 2013**

## **5.3.6 Multilevel Feedback Queue**

- A process can move between the various queues; **aging** can be implemented this way
- Multilevel-feedback-queue scheduler defined by the following **parameters**:
	- number of queues
	- scheduling algorithms for each queue
	- method used to determine when to upgrade a process
	- method used to determine when to demote a process
	- method used to determine which queue a process will enter when that process needs service



#### **Example of Multilevel Feedback Queue**

- Three queues:
	- *Q*<sup>0</sup> RR with time quantum 8 milliseconds
	- $Q_1$  RR time quantum 16 milliseconds
	- $Q_2$  FCFS
- **Scheduling** 
	- A new job enters queue  $Q_0$  which is served **FCFS** 
		- ▶ When it gains CPU, job receives 8 milliseconds
		- If it does not finish in 8 milliseconds, ic moved to queue *Q*<sup>1</sup>
	- At Q<sub>1</sub> job is again served FCFS and receiv 16 additional milliseconds
		- If it still does not complete, it is preempted and moved to queue  $Q_2$







#### **5.4 THREAD SCHEDULING**



# **5.4.1 Contention Scope**

- Distinction between user-level and kernel-level threads
- When threads supported, threads scheduled, not processes
- Many-to-one and many-to-many models, thread library schedules userlevel threads to run on LWP
	- Known as **process-contention scope (PCS)** since scheduling competition is within the process
	- Typically done via priority set by programmer
- Kernel thread scheduled onto available CPU is **system-contention scope (SCS)** – competition among all threads in system
	- Systems using the one-to-one model (Section 4.3.2), such as Windows, Linux, and Solaris, schedule threads using only SCS.





- API allows specifying either PCS or SCS during thread creation
	- PTHREAD\_SCOPE\_PROCESS schedules threads using PCS scheduling
	- PTHREAD\_SCOPE\_SYSTEM schedules threads using SCS scheduling
- Can be limited by OS Linux and Mac OS X only allow PTHREAD\_SCOPE\_SYSTEM



### **Pthread Scheduling API**

```
#include <pthread.h>
#include <stdio.h> 
#define NUM_THREADS 5 
int main(int argc, char *argv[]) { 
    int i, scope;
   pthread t tid[NUM THREADS];
   pthread attr t attr;
   /* get the default attributes */pthread attr init(&attr);
   /* first inquire on the current scope */if (pthread attr getscope(&attr, &scope) != 0)
      fprintf(stderr, "Unable to get scheduling scope\langle n'' \rangle;
    else { 
       if (scope == PTHREAD_SCOPE_PROCESS) 
         printf("PTHREAD SCOPE PROCESS");
       else if (scope == PTHREAD_SCOPE_SYSTEM) 
         printf("PTHREAD SCOPE SYSTEM");
       else
         fprintf(stderr, "Illegal scope value.\n");
 }
```


```
/* set the scheduling algorithm to PCS or SCS */pthread attr_setscope(&attr, PTHREAD_SCOPE_SYSTEM);
   \frac{1}{x} create the threads \frac{x}{x}for (i = 0; i < NUM THREADS; i^{++})
      pthread create(&tid[i], &attr,runner, NULL);
    /* now join on each thread */
   for (i = 0; i < NUM THREADS; i++)
      pthread join(tid[i], NULL);
} 
/* Each thread will begin control in this function */void *runner(void *param)
\{\frac{1}{2} do some work ... \frac{1}{2}pthread exit(0);
}
```




#### **5.5 MULTIPLE-PROCESSOR SCHEDULING**



#### **5.5.1 Approaches to Multiple Processor Scheduling**

- CPU scheduling more complex when multiple CPUs are available
- **Homogeneous processors** within a multiprocessor
- **Asymmetric multiprocessing**  only one processor accesses the system data structures, alleviating the need for data sharing
- **Symmetric multiprocessing (SMP)** each processor is selfscheduling, all processes in common ready queue, or each has its own private queue of ready processes
	- Currently, most common





- **Processor affinity** process has affinity for processor on which it is currently running
	- **soft affinity**
	- **hard affinity**
	- Variations including **processor sets**



Note that memory-placement algorithms can also consider affinity





- If SMP, need to keep all CPUs loaded for efficiency
- **Load balancing** attempts to keep workload evenly distributed
- **Push migration**  periodic task checks load on each processor, and if found pushes task from overloaded CPU to other CPUs
- **Pull migration** idle processors pulls waiting task from busy processor



## **5.5.4 Multicore Processors**

- Recent trend to place multiple processor cores on same physical chip
- Faster and consumes less power
- Multiple threads per core also growing
	- Takes advantage of **memory stall** to make progress on another thread while memory retrieve happens



## **Multithreaded Multicore System**



**Operating System Concepts – 9**

**th Edition 41 Silberschatz, Galvin and Gagne © 2013**